

Corning® LSE™ Digital Dry Bath Heaters

CORNING



The Corning Digital Dry Bath Heaters are available in single, dual, and four block configurations and provide a broad temperature range up to 150°C, which makes them useful for a variety of applications in molecular biology, histology, clinical, environmental, and industrial laboratories. They have been designed to incorporate the best combination of features including block capacity, dual displays, and an external temperature probe that gives life science researchers the confidence and efficiency they need when working with precious samples.

Features

- ▶ Single, dual, and four block capacity to maximize sample processing
- ▶ Dual display allows for easy monitoring of temperature and time
- ▶ USB connectivity enables traceability of data
- ▶ Molded block chamber provides excellent temperature uniformity

Specifications

Dimensions (W x D x H)	Single block: 8.3 x 12.4 x 4.7 in. (21 x 29 x 12 cm) Dual block: 8.3 x 12.4 x 4.7 in. (21 x 29 x 12 cm) Four block: 8.3 x 16.3 x 4.7 in. (21 x 39 x 12 cm)
---------------------------	--

Weight	Single block: 7.0 lbs. (3.2 kg) Dual block: 7.0 lbs. (3.2 kg) Four block: 9.6 lbs. (4.4 kg)
--------	---

Capacity	1, 2, 4 blocks
----------	----------------

Temperature range	Ambient +5°C to 150°C
-------------------	-----------------------

Temperature accuracy	± 0.3°C
----------------------	---------

Temperature uniformity	± 0.2°C
------------------------	---------

Temperature increments	0.1°C
------------------------	-------

Display	Digital, dual
---------	---------------

External temperature probe	See optional accessories
----------------------------	--------------------------

Chamber construction	Uniformly molded
----------------------	------------------

Block lid	Included
-----------	----------

Interface	USB
-----------	-----



Digital dry bath heater accessories

Ordering Information

Corning® LSE™ Digital Dry Bath Heaters

Cat. No.	Description	Qty/ Cs
6875-SB	LSE digital dry bath heater, single block, 120V	1
6885-DB	LSE digital dry bath heater, dual block, 120V	1
6895-FB	LSE digital dry bath heater, four block, 120V	1
6876-SB	LSE digital dry bath heater, single block, 230V, EU plug	1
6886-DB	LSE digital dry bath heater, dual block, 230V, EU plug	1
6896-FB	LSE digital dry bath heater, four block, 230V, EU plug	1
6877-SB	LSE digital dry bath heater, single block, 230V, UK plug	1
6887-DB	LSE digital dry bath heater, dual block, 230V, UK plug	1
6897-FB	LSE digital dry bath heater, four block, 230V, UK plug	1
6878-SB	LSE digital dry bath heater, single block, 100V	1
6888-DB	LSE digital dry bath heater, dual block, 100V	1
6898-FB	LSE digital dry bath heater, four block, 100V	1

Digital Dry Bath Heater Accessories

Cat. No.	Description	Qty/ Cs
480116	Single block* for 48 x 0.2 mL PCR tubes or 6 x 0.2 mL strips	1
480117	Single block* for 20 x 2.0 mL tubes	1
480118	Single block* for 24 x 0.5 mL tubes	1
480119	Single block* for 24 x 1.5 mL tubes	1
480120	Single block* for 35 x 6 mm tubes	1
480121	Single block* for 20 x 10 mm tubes	1
480122	Single block* for 20 x 12 mm tubes	1
480123	Single block* for 20 x 13 mm tubes	1
480124	Single block* for 12 x 15 mL centrifuge tubes	1
480125	Single block* for 12 x 16 mm tubes	1
480126	Single block* for 12 x 17 mm tubes	1
480127	Single block* for 6 x 20 mm tubes	1
480128	Single block* for 6 x 25 mm tubes	1
480129	Single block* for 5 x 50 mL centrifuge tubes	1
480130	Single block, 96-well PCR microplate, skirted or nonskirted (for single block unit only)	1
480131	Dual block, 96-well microplate or 4 slides (for dual block unit only)	1
480132	Dual block, 96-well PCR microplate, skirted or nonskirted (for dual block unit only)	1
480133	Dual block, 384-well PCR microplate (for dual block unit only)	1

*Can be utilized with the single, dual, and four block units.

For more specific information on claims, visit the Certificates page at www.corning.com/lifesciences.

Warranty/Disclaimer: Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications.

For additional product or technical information, visit www.corning.com/lifesciences or call 800.492.1110.

Outside the United States, call +1.978.442.2200 or contact your local Corning sales office.

Corning Incorporated Life Sciences

836 North St.
Building 300, Suite 3401
Tewksbury, MA 01876
t 800.492.1110
t 978.442.2200
f 978.442.2476

www.corning.com/lifesciences

Worldwide Support Offices

ASIA/PACIFIC

Australia/New Zealand
t 61 427286832

China
t 86 21 3338 4338
f 86 21 3338 4300

India
t 91 124 4604000
f 91 124 4604099

Japan

t 81 3-3586 1996
f 81 3-3586 1291

Korea

t 82 2-796-9500
f 82 2-796-9300

Singapore

t 65 6572-9740
f 65 6861-2913

Taiwan

t 886 2-2716-0338
f 886 2-2516-7500

EUROPE

France

t 0800 916 882
f 0800 918 636

Germany

t 0800 101 1153
f 0800 101 2427

The Netherlands

t 020 655 79 28
f 020 659 76 73

United Kingdom

t 0800 376 8660
f 0800 279 1117

All Other European Countries

t 31 (0) 20 659 60 51
f 31 (0) 20 659 76 73

LATIN AMERICA grupoLA@corning.com

Brasil

t (55-11) 3089-7400

Mexico

t (52-81) 8158-8400

CORNING | **FALCON** | **AXYGEN** | **GOSSELIN** | **PYREX**